



(slika je simbolična)

Filter regulator »multifix«, 40 µm, Velikost 5, G 1, 0.5 - 10 bar

Kategorija: [Filter regulator with metal bowl and sight glass](#)
Šifra: **100497RIE**

Kratek opis

Filter regulator »multifix« with metal container, Viewing tube and press. gauge, 40 µm, Size 5, G 1, Input pressure max. 20 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.
The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Max. notranja poraba zraka	0,5 l/min (depending on secondary pressure) At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	G 1
Navoj	Semi-automatic
Odtok kondenzata	Aluminium
Ohišje	Yes
Poraba zraka	Metal container with viewing tube
Posoda	multifix
Serija	NBR
Tesnilo	POM-brass
Vzmet pokrova motorja	
Min. krmilno območje [bar]	0.5
Velikost	5
Max. krmilno območje [bar]	10
Zaslona manometra max. [bar]	16
Max. vhodni tlak [bar]	20
DN	25
Rang filtra [µm]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	100.0
C [mm]	128.0
D [mm]	255.7
B [mm]	383.7
Pretok [l/min]	15000