



## Filter regulator »Stinard«, PC zbiralnik, 40 µm, Velikost 4, G 1

Kategorija: [Filter regulator with polycarbonate bowl](#)  
Šifra: **174093RIE**

(slika je simbolična)

### Kratek opis

Filter regulator »Standard«, PC container, press. gauge, 40 µm, Size 4, G 1, PE max. 16 bar, Control range 0.5-10 bar, pilot cont.

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1                                                                  |
| Odtok kondenzata             | Semi-automatic                                                       |
| Ohišje                       | Aluminium, painted silver                                            |
| Posoda                       | Polycarbonate container                                              |
| Serija                       | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 4                                                                    |
| Max. krmilno območje [bar]   | 10                                                                   |
| Max. vhodni tlak [bar]       | 16                                                                   |
| Zaslona manometra max. [bar] | 16                                                                   |
| DN                           | 25                                                                   |
| Rang filtra [µm]             | 40                                                                   |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| A [mm]                       | 125.0                                                                |
| C [mm]                       | 129.0                                                                |
| D [mm]                       | 263.0                                                                |
| Pretok [l/min]               | 12000                                                                |