

Datum: 03.05.2026



(slika je simbolična)

## [Filter regulator »variobloc« s kovinsko posodo, Velikost 2, G 3/4](#)

Kategorija: [Filter regulator, metal bowl, incl. sight glass](#)Šifra: **125313RIE**

### Kratek opis

Filter regulator »variobloc«, Metal container incl. viewing tube and pressure gauge, Size 2, G 3/4, Input pressure max. 20 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Membrane                     | NBR   |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 3/4   |
| Odtok kondenzata             | Manual  |
| Ohišje                       | Die-cast zinc   |
| Posoda                       | Metal container with viewing tube                                     |
| Serija                       | variobloc   |
| Tesnilo                      | NBR   |
| Vzmet pokrova motorja        | POM   |
| Min. krmilno območje [bar]   | 0.5   |
| Velikost                     | 2   |
| Max. krmilno območje [bar]   | 10  |
| Zaslon manometra max. [bar]  | 10  |
| Max. vhodni tlak [bar]       | 20  |
| Rang filtra [ $\mu$ m]       | 40  |
| A [mm]                       | 70.0  |
| Max. sobna temperatura [°C]  | 80  |
| Max. temperatura medija [°C] | 80  |
| C [mm]                       | 98.0  |
| B [mm]                       | 273.0   |
| Pretok [l/min]               | 6500  |