

Datum: 04.06.2026



Filter regulator »variobloc« z zaščitno kletko, Velikost 1, G 3/8

Kategorija: [Filter regulator with PC bowl and bowl guard](#)Šifra: **124782RIE**

(slika je simbolična)

Kratek opis

Filter regulator »variobloc«, PC container, Protective cage and pressure gauge, Size 1, G 3/8, Input pressure max. 16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

| | |
|------------------------------|---|
| Membrane | NBR |
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Manual |
| Ohišje | Die-cast zinc Polycarbonate container with protective cage |
| Posoda | variobloc |
| Serija | NBR |
| Tesnilo | POM |
| Vzmet pokrova motorja | 0.5 |
| Min. krmilno območje [bar] | 1 |
| Velikost | 10 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 16 |
| Max. vhodni tlak [bar] | 40 |
| Rang filtra [μ m] | 48.0 |
| A [mm] | 50 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| C [mm] | 68.0 |
| B [mm] | 203.0 |
| Pretok [l/min] | 3000 |