

Datum: 19.09.2024



(slika je simbolična)

[Filter-regulator z PC zbir.Vel.1,G 1/4, 0.5 - 10 bar](#)

Kategorija: [Combined service unit, PC bowl, manual drain](#)Šifra: **101088RIE**

Kratek opis

Combi-service unit with PC container, manual bleeder valve, Size 1, G 1/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar

A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob down.

Oil can be filled under pressure.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/4 |
| Odtok kondenzata | Manual drain valve |
| Ohišje | Die-cast zinc |
| Posoda | Polycarbonate container |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Vzmet pokrova motorja | PA |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 1 |
| Max. krmilno območje [bar] | 10 |
| Max. vhodni tlak [bar] | 16 |
| Rang filtra [μ m] | 40 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| A [mm] | 67.0 |
| C [mm] | 68.5 |
| B [mm] | 217.0 |
| Pretok [l/min] | 1400 |