

Datum: 13.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

Filter-regulator Zašč. kletka Vel. 2, G 3/4, 0.5 - 16 bar

Kategorija: [Combined service unit, PC bowl and bowl guard](#)
Šifra: **101105RIE**

(slika je simbolična)

Kratek opis

Combi-service unit with PC container and Protective cage,
Size 2, G 3/4, Input pressure max. 16 bar, Control range 0.5
- 16 bar

A filter, pressure regulator and oil-mist lubricator combined
in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob
down.

Oil can be filled under pressure.

Tehnične Specifikacije

| | |
|---------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p =$ 1 bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Manual drain valve |
| Ohišje | Die-cast zinc Polycarbonate container with protective cage |
| Posoda | NBR |
| Tesnilo | PA |
| Vidna kupola | PA |
| Vzmet pokrova motorja | PA |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 2 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 16 |
| Rang filtra [μ m] | 40 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| C [mm] | 96.5 |
| A [mm] | 97.0 |
| B [mm] | 296.5 |
| Pretok [l/min] | 2800 |