

Datum: 25.06.2026



(slika je simbolična)

## Filter »variobloc«PC zbir.Zašč. kletkaVel. 2G 3/4

Kategorija: [Filter with polycarbonate bowl and bowl guard](#)Šifra: **124770RIE**

### Kratek opis

Filter »variobloc«, Polycarbonate container and protective cage, Size 2, G 3/4, Input pressure max. 16 bar, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Merjenje pretoka             | At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 3/4   |
| Odtok kondenzata             | Manual  |
| Ohišje                       | Die-cast zinc   |
| Posoda                       | Polycarbonate container with protective cage          |
| Serija                       | variobloc   |
| Tesnilo                      | NBR   |
| Velikost                     | 2   |
| Max. vhodni tlak [bar]       | 16  |
| C [mm]                       | 26.0  |
| Rang filtra [ $\mu$ m]       | 40  |
| Max. sobna temperatura [°C]  | 50  |
| Max. temperatura medija [°C] | 50  |
| A [mm]                       | 70.0  |
| B [mm]                       | 202.0   |
| Pretok [l/min]               | 3500  |