



(slika je simbolična)

Filter »variobloc« z PC zbiralnik, Velikost 1, G 1/4

Kategorija: [Filter with polycarbonate bowl](#)
Šifra: **100678RIE**

Kratek opis

Filter »variobloc«, PC container, Size 1, G 1/4, Input pressure max. 16 bar, Med. / ambient temp. max. 50 °C, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/4 |
| Odtok kondenzata | Manual |
| Ohišje | Die-cast zinc |
| Posoda | Polycarbonate container |
| Serijski | variobloc |
| Tesnilo | NBR |
| Velikost | 1 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 22.0 |
| Rang filtra [μ m] | 40 |
| A [mm] | 48.0 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| B [mm] | 155.0 |
| Pretok [l/min] | 1800 |