

Datum: 25.06.2026



(slika je simbolična)

Filter »variobloc« z PC zbiralnik, Velikost 2, G 1

Kategorija: [Filter with polycarbonate bowl](#)
Šifra: **100682RIE**

Kratek opis

Filter »variobloc«, PC container, Size 2, G 1, Input pressure max. 16 bar, Med. / ambient temp. max. 50 °C, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Serijska	variobloc
Tesnilo	NBR
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	26.0
Rang filtra [μ m]	40
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	124.0
B [mm]	202.0
Pretok [l/min]	3500