

Datum: 17.03.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Filter z aktivnim ogljem brez diferencialnega manometra, G 1/2

Kategorija: [Activated carbon filter without diff. press. gauge](#)  
Šifra: **101586RIE**

### Kratek opis

Active charcoal filter without differential pressure gauge, 0.005 mg/m<sup>3</sup>, G 1/2, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C  
For adsorbing vaporous media.  
A micro-filter must be connected upstream if dried air is not available.

### Tehnične Specifikacije

Element filtra	Activated carbon
Merjenje pretoka	At P <sub>1</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.5%
Navoj	G 1/2
Ohišje	Aluminium
Posoda filtra	Aluminium
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.005
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	16
C [mm]	57.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	83.0
B2 [mm]	245.0
D [mm]	263.0
Pretok [l/min]	500