



(slika je simbolična)

## Filter z aktivnim ogljem brez diferencialnega manometra, G 2

Kategorija: [Activated carbon filter without diff. press. gauge](#)Šifra: **101591RIE**

### Kratek opis

Active charcoal filter without differential pressure gauge,  
0.005 mg/m<sup>3</sup>, G 2, Input pressure 4 - 16 bar, Temp. 5 °C to  
60 °C

For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not  
available.

### Tehnične Specifikacije

Element filtra	Activated carbon
Merjenje pretoka	At P <sub>1</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.5%
Navoj	G 2
Ohišje	Aluminium
Posoda filtra	Aluminium
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.005
D [mm]	1.148.0
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	16
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	72.0
A [mm]	118.0
B2 [mm]	720.0
Pretok [l/min]	6650