



Filter z aktivnim ogljem»FUTURA«Kov. pos.Vel. 4, G 1

Kategorija: [Activated carbon filter, metal bowl, sight glass](#)
Šifra: **156649RIE**

(slika je simbolična)

Kratek opis

Active charcoal filter »FUTURA« with metal container and viewing tube, 0.005 mg/m³, Size 4, G 1, Input pressure 0 - 16 bar
Activated carbon filters in modern design for compliance with strict compressed air purity requirements.
Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P ₂ = 6 bar and pressure drop Δp = 0.2 bar
Merjenje pretoka	G 1
Navoj	PA66 GF60
Ohišje	Metal container with viewing tube
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	4
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	58.0
A [mm]	85.0
B [mm]	241.0
Pretok [l/min]	2500