



(slika je simbolična)

## Filter z aktivnim ogljem»FUTURA«Kov. pos.Vel.4, G 3/4

Kategorija: [Activated carbon filter, metal bowl, sight glass](#)Šifra: **156648RIE**

### Kratek opis

Active charcoal filter »FUTURA« with metal container and viewing tube, 0.005 mg/m<sup>3</sup>, Size 4, G 3/4, Input pressure 0 - 16 bar

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m<sup>3</sup> from compressed air and gases.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.2 bar
Merjenje pretoka	G 3/4 PA66 GF60 Metal container with viewing tube
Navoj	Material: Die-cast zinc FUTURA
Ohišje	Compressed air, neutral gases
Posoda	
Priključni navoj	
Serijska	
Srednje	
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.005
Velikost	4
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	58.0
A [mm]	85.0
B [mm]	241.0
Pretok [l/min]	2500