



(slika je simbolična)

Filter z aktivnim ogljem»FUTURA« z PC zbir.Vel.1,G 3/8

Kategorija: [Activated carbon filter, PC bowl, bowl guard](#)
Šifra: **100192RIE**

Kratek opis

Active charcoal filter »FUTURA« with PC container and protective cage, 0.005 mg/m³, Size 1, G 3/8, Input pressure 0 - 16 bar

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P ₂ = 6 bar and pressure drop Δ _p = 0.2 bar
Merjenje pretoka	G 3/8 PA66 GF60
Navoj	Polycarbonate container with protective cage
Ohišje	Material: Die-cast zinc FUTURA
Posoda	Compressed air, neutral gases
Priključni navoj	
Serijska	
Srednje	
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	1
Max. vhodni tlak [bar]	16
C [mm]	34.0
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	157.0
Pretok [l/min]	470