

Datum: 07.03.2026



(slika je simbolična)

Filter z aktivnim ogljem »FUTURA« z PC zbir.Vel.2,G 1/2

Kategorija: [Activated carbon filter, PC bowl, bowl guard](#)
Šifra: **100194RIE**

Kratek opis

Active charcoal filter »FUTURA« with PC container and protective cage, 0.005 mg/m³, Size 2, G 1/2, Input pressure 0 - 16 bar

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P ₂ = 6 bar and pressure drop Δ _p = 0.2 bar
Merjenje pretoka	G 1/2 PA66 GF60 Polycarbonate container with protective cage
Navoj	Material: Die-cast zinc FUTURA
Ohišje	Compressed air, neutral gases
Posoda	
Priključni navoj	
Serijska	
Srednje	
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	42.5
Max. temperaturno območje [°C]	50
A [mm]	63.0
B [mm]	183.5
Pretok [l/min]	1700