



(slika je simbolična)

## Filter z aktivnim ogljem»FUTURA« z PC zbir.Vel.2,G 3/8

Kategorija: [Activated carbon filter, PC bowl, bowl guard](#)  
Šifra: **100193RIE**

### Kratek opis

Active charcoal filter »FUTURA« with PC container and protective cage, 0.005 mg/m<sup>3</sup>, Size 2, G 3/8, Input pressure 0 - 16 bar

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m<sup>3</sup> from compressed air and gases.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.2 bar
Merjenje pretoka	G 3/8 PA66 GF60
Navoj	Polycarbonate container with protective cage
Ohišje	Material: Die-cast zinc FUTURA
Posoda	Compressed air, neutral gases
Priključni navoj	
Serijska	
Srednje	
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.005
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	42.5
Max. temperaturno območje [°C]	50
A [mm]	63.0
B [mm]	183.5
Pretok [l/min]	1700