



## Filter z aktivnim ogljem »multifix-mali«, Kovinska posoda, G 1/8

Kategorija: [Activated carbon filter with metal bowl](#)  
Šifra: **100378RIE**

(slika je simbolična)

### Kratek opis

Active charcoal filter »multifix-mini«, metal container, 0.005 mg/m<sup>3</sup>, G 1/8, Input press. max. 16 bar, Med./ambient temp. max.60°C

For filtering odours out of compressed air.

The activated carbon absorbs the oil vapour molecules contained in the compressed air.

A separate filter route prevents activated carbon particles from entering the air flow.

### Tehnične Specifikacije

|  |  |
|--|--|
| Element filtra                               | Activated carbon-POM   |
| Merjenje pretoka                             | At P <sub>1</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.2 bar |
| Navoj  | G 1/8  |
| Ohišje                                       | Die-cast zinc  |
| Posoda                                       | Metal container  |
| Serijska                                     | multifix-mini  |
| Tesnilo                                      | NBR  |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ] | 0.005  |
| DN   | 5  |
| C [mm]                                       | 12.3   |
| Max. vhodni tlak [bar]                       | 16   |
| A [mm]                                       | 40.0   |
| Max. sobna temperatura [°C]                  | 60   |
| Max. temperatura medija [°C]                 | 60   |
| D [mm]                                       | 85.0   |
| B [mm]                                       | 97.3   |
| Pretok [l/min]                               | 310  |