

Datum: 31.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Filter z aktivnim ogljem »variobloc« Kov. pos.Vel.1,G 3/8

Kategorija: [Activated carbon filter with metal bowl](#)  
Šifra: **125331RIE**

### Kratek opis

Active charcoal filter »variobloc« with metal container incl. viewing tube, 0.003 mg/m<sup>3</sup>, Size 1, G 3/8, Input pressure max. 20 bar  
Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

### Tehnične Specifikacije

Kakovost zraka po ISO 8573.1	Class 1 dirt, class 1 oil
Merjenje pretoka	At P <sub>1</sub> = 7 bar and pressure drop Δp = 0,2 bar
Navoj	G 3/8
Posoda	Metal container with viewing tube
Serija	variobloc
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.003
Velikost	1
Max. vhodni tlak [bar]	20
C [mm]	22.0
A [mm]	48.0
Max. temperatura medija [°C]	50
Max. sobna temperatura [°C]	80
B [mm]	142.0
Pretok [l/min]	1000