



(slika je simbolična)

Filter z aktivnim ogljem »variobloc«PC zbir.Vel. 2G 3/4

Kategorija: [Activated carbon filter with polycarbonate bowl](#)
Šifra: **100695RIE**

Kratek opis

Active charcoal filter »variobloc« with PC container, 0.003 mg/m³, Size 2, G 3/4, Input pressure max. 16 bar, Temp. max. 50 °C

Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Tehnične Specifikacije

| | |
|--|--|
| Kakovost zraka po ISO 8573.1 | Class 1 dirt, class 1 oil |
| Merjenje pretoka | At P ₁ = 7 bar and pressure drop Δp = 0,2 bar |
| Navoj | G 3/4 |
| Posoda | Polycarbonate container variobloc |
| Serija | |
| Vsebnost olja v ostanku [mg/m ³] | 0.003 |
| Velikost | 2 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 26.0 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| A [mm] | 70.0 |
| B [mm] | 193.0 |
| Pretok [l/min] | 1300 |