

Datum: 24.06.2026



## Filter z aktivnim ogljem »variobloc« Zašč. kletka Vel.2,G 1/2

Kategorija: [Activated carbon filter with PC bowl, bowl guard](#)  
Šifra: **125327RIE**

(slika je simbolična)

### Kratek opis

Active charcoal filter »variobloc« with PC container and protective cage, 0.003 mg/m<sup>3</sup>, Size 2, G 1/2, Input pressure max. 16 bar

Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

### Tehnične Specifikacije

Kakovost zraka po ISO 8573.1	Class 1 dirt, class 1 oil
Merjenje pretoka	At P <sub>1</sub> = 7 bar and pressure drop Δp = 0,2 bar
Navoj	G 1/2
Posoda	Polycarbonate container with protective cage variobloc
Serija	
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.003
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	26.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	70.0
B [mm]	193.0
Pretok [l/min]	1200