



(slika je simbolična)

Filter z aktivnim ogljem z diferencialnim manometrom, G 1/2

Kategorija: [Activated carbon filter with diff. pressure gauge](#)Šifra: **101578RIE**

Kratek opis

Active charcoal filter with differential pressure gauge, 0.005 mg/m³, G 1/2, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not available.

Tehnične Specifikacije

Element filtra	Activated carbon
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 0.5%
Navoj	G 1/2
Ohišje	Aluminium
Posoda filtra	Aluminium
Vsebnost olja v ostanku [mg/m ³]	0.005
Max. označeni razpon diferencialnega manometra [bar]	2
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	16
C [mm]	57.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	83.0
B2 [mm]	245.0
D [mm]	263.0
B1 [mm]	344.0
Pretok [l/min]	500