



(slika je simbolična)

Filter z aktivnim ogljem z diferencialnim manometrom, G 3/8

Kategorija: [Activated carbon filter with diff. pressure gauge](#)
Šifra: **101577RIE**

Kratek opis

Active charcoal filter with differential pressure gauge, 0.005 mg/m³, G 3/8, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C For adsorbing vaporous media.
A micro-filter must be connected upstream if dried air is not available.

Tehnične Specifikacije

| | |
|--|---|
| Element filtra | Activated carbon |
| Merjenje pretoka | At P ₁ = 6 bar and pressure drop Δ _p = 0.5% |
| Navoj | G 3/8 |
| Ohišje | Aluminium |
| Posoda filtra | Aluminium |
| Vsebnost olja v ostanku [mg/m ³] | 0.005 |
| Max. označeni razpon diferencialnega manometra [bar] | 2 |
| Min. vhodni tlak [bar] | 4 |
| Min. sobna temperatura [°C] | 5 |
| Min. temperatura medija [°C] | 5 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 57.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 83.0 |
| B2 [mm] | 245.0 |
| D [mm] | 263.0 |
| B1 [mm] | 344.0 |
| Pretok [l/min] | 500 |