

Datum: 13.06.2026



(slika je simbolična)

Glicerinski man.cent. priklop zadaj G 1/4, -1/+3 bar, Ø 63

Kategorija: [Wika](#)Šifra: **102091RIE**

Kratek opis

Glycerine pressure gauge, plastic housing, Connection, rear, centric, G 1/4, Goods class 2.5, Measurement range -1 / +3 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

| | |
|--|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Merilno območje min. psi | -14.5 |
| Merilno območje min. bar | -1 |
| Material Prozessanschluss | Copper alloy |
| Merilni element | Copper alloy |
| Ohišje | Plastic, black (with panel-mounting bezel) |
| Položaj povezave | rear, central |
| Povezava | G 1/4 |
| Prednje steklo | PMMA, welded to housing |
| Premikanje | Copper alloy |
| Spodnja/Zgornja meja območja | Vacuum/Positive pressure |
| Stopnja rasti na območju skale - bar [bar] | 0.2 |
| Razred točnosti | 2.5 |
| Merilno območje max. bar | 3 |
| Merilno območje max. psi | 44 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| Premer [mm] | 63 |
| Vrsta | 113.13 |