



## Glicerinski man.ekscent. priklop zadaj G1/2, 0-160 bar, Ø100

Kategorija: [Wika](#)  
Šifra: **102242RIE**

(slika je simbolična)

### Kratek opis

Glycerine pressure gauge, metal housing, Connection, rear, eccentric, G 1/2, Goods class 1.0, Measurement range 0-160 bar, Ø 100

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|  |                   |
|--|-------------------|
| Min. sobna temperatura [°C]                | -20               |
| Min. temperatura medija [°C]               | -20               |
| Material Prozessanschluss                  | Copper alloy      |
| Merilni element                            | CrNi steel 1.4571 |
| Ohišje                                     | Hot-pressed brass |
| Položaj povezave                           | rear, excentrical |
| Povezava                                   | G 1/2             |
| Prednje steklo                             | Plexiglass        |
| Premikanje                                 | Copper alloy      |
| Spodnja/Zgornja meja območja               | Positive pressure |
| Stisnjen okvir                             | CrNi steel        |
| Razred točnosti                            | 1.0               |
| Stopnja rasti na območju skale - bar [bar] | 5                 |
| Max. sobna temperatura [°C]                | 60                |
| Max. temperatura medija [°C]               | 60                |
| Premer [mm]                                | 100               |
| Merilno območje max. bar                   | 160               |
| Vrsta                                      | 213.40            |