



Glicerinski manometer, CrNi jeklo, G 1/2, -1 / 0 bar, Ø 100

Kategorija: [Wika](#)
Šifra: **134031RIE**

(slika je simbolična)

Kratek opis

Glycerine pressure gauge CrNi steel design, Connection, rear, eccentric, G 1/2, Goods class 1.0, Measure. range -1 / 0 bar, Ø 100

Glycerine-filled bourdon-tube pressure gauge, CrNi steel type.

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

Tehnične Specifikacije

| | |
|--------------------------------------------|------------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Merilno območje min. bar | -1 |
| Material | CrNi steel |
| Material Prozessanschluss | CrNi steel |
| Položaj povezave | rear, excentrical |
| Povezava | G 1/2 |
| Prednje steklo | Laminated safety glass |
| Spodnja/Zgornja meja območja | Vacuum |
| Stopnja rasti na območju skale - bar [bar] | 0.02 |
| Razred točnosti | 1.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 100 |
| Premer [mm] | 100 |
| Vrsta | 233.50 |