

Datum: 02.07.2026



(slika je simbolična)

## Glicerinski manometer, CrNi jeklo, G 1/4, -1 / 0 bar, Ø 63

Kategorija: [Wika](#)  
Šifra: **102376RIE**

### Kratek opis

Glycerine pressure gauge, CrNi steel safety design,  
Connection radial bottom, G 1/4, Measurement range -1 / 0  
bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge, CrNi steel  
type, with solid baffle wall and blow-out (safety housing).  
Suitable for gaseous or liquid, corrosive and crystallising  
media which do not have high viscosity, also in corrosive  
atmosphere.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merilno območje min. bar	-1
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/4
Prednje steklo	Polycarbonate
Spodnja/Zgornja meja območja	Vacuum
Stopnja rasti na območju skale - bar [bar]	0.05
Razred točnosti	1.6
Max. sobna temperatura [°C]	60
Premer [mm]	63
Max. temperatura medija [°C]	100
Vrsta	233.30