

Datum: 10.05.2026



Glicerinski manometer »pressure line« G 1/2, 0-400bar/6000 psi

Kategorija: [Glycerine pressure gauge, conn. radial on bottom](#)
Šifra: **116324RIE**

(slika je simbolična)

Kratek opis

Glycerine press. gauge »pressure line« Connection radial bottom, G 1/2, Goods class 1.6, Measurement range 0-400bar/6000 psi, Ø100
Low-priced series of high-quality, glycerine-filled pressure gauges with stainless steel housing for all applications involving measurements in areas with high dynamic pressure loads and vibration levels.
Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Brass
Ohišje	Stainless steel
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Glass
Premikanje	Brass
Različica	Bourdon-tube pressure gauge with glycerine filling
Razred točnosti	1.6
Stopnja rasti na območju skale - bar [bar]	10
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premer [mm]	100
Merilno območje max. bar	400