



## Glicerinski manometer »pressure line« G 1/4, 0-400bar/6000 psi

Kategorija: [Glycerine pressure gauge, conn. radial on bottom](#)  
Šifra: **116316RIE**

(slika je simbolična)

### Kratek opis

Glycerine press. gauge »pressure line« Connection radial bottom, G 1/4, Goods class 1.6, Measurement range 0-400 bar/6000 psi, Ø63

Low-priced series of high-quality, glycerine-filled pressure gauges with stainless steel housing for all applications involving measurements in areas with high dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                                                    |
|--------------------------------------------|----------------------------------------------------|
| Min. sobna temperatura [°C]                | -20                                                |
| Min. temperatura medija [°C]               | -20                                                |
| Material Prozessanschluss                  | Copper alloy                                       |
| Merilni element                            | Brass                                              |
| Ohišje                                     | Stainless steel                                    |
| Položaj povezave                           | radial on bottom                                   |
| Povezava                                   | G 1/4                                              |
| Prednje steklo                             | Glass                                              |
| Premikanje                                 | Brass                                              |
| Različica                                  | Bourdon-tube pressure gauge with glycerine filling |
| Razred točnosti                            | 1.6                                                |
| Stopnja rasti na območju skale - bar [bar] | 10                                                 |
| Max. sobna temperatura [°C]                | 60                                                 |
| Max. temperatura medija [°C]               | 60                                                 |
| Premer [mm]                                | 63                                                 |
| Merilno območje max. bar                   | 400                                                |