TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 16.11.2026



(slika je simbolična)

Hidravlična spojkaSerija AI.D. 13,Med.G 1/2 N.N.

Kategorija: Hydraulic coupling, female
Šifra: **107723RIE**

Kratek opis

Hydraulic coupling, Series A, I.D. 13, Brass, G 1/2 IT, Operating pressure max. 250 bar, Operating temp. -30 °C to 100 °C
Acc. to ISO 7241-1, A Series.
This coupling series combines an extremely small pressure drop with maximum hydraulic power transmission.
Interchangeable with all couplings and plugs manufactured according to the above standard.
The patented pressure eliminator permits disconnection even if back pressure has built up (up to 200 bar).
The pressure eliminator can be used in all applications where there is a risk of pressure build-up after the line has been separated. It allows effortless connection under pressure.
The mating part must be pressureless in order for the eliminator to function optimally.
Areas of application: Agricultural machines, construction machines, municipal engineering, transportation engineering, industrial plant.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-30
Krogla	Stainless steel
Ohišje	Brass
Povezava	G 1/2 IT
Sprostitveni rokav	Nickel-plated brass
Tesnilo	NBR
Ventil	Hard drawn brass
Vzmet	Stainless steel
a/f [mm]	27
Volumski pretok (olje) [l/min]	30
Dolžina [mm]	63.0
Max. delovna temperatura [°C]	100
Max. obratovalni tlak [bar]	250