

Datum: 26.04.2026



(slika je simbolična)

Hidravlična spojka Serija B, poniklj. Med.G 1/2 N.N.

Kategorija: [Hydraulic couplings, female](#)
Šifra: **107730RIE**

Kratek opis

Hydraulic coupling, Series B, nickel-plated brass, G 1/2 IT, I.D. 12.5, Operating pressure max. 300 bar
Acc. to ISO 7241-1, B Series.

This coupling series combines an extremely small pressure drop with maximum hydraulic power transmission.

Interchangeable with all couplings and plugs manufactured according to the above standard.

The patented pressure eliminator permits disconnection even if back pressure has built up (up to 200 bar).

The pressure eliminator can be used in all applications where there is a risk of pressure build-up after the line has been separated. It allows effortless connection under pressure.

The mating part must be pressureless in order for the eliminator to function optimally.

Areas of application: chemical industry, food technology, automotive, offshore.

Tehnične Specifikacije

| | |
|--------------------------------|---------------------|
| Min. delovna temperatura [°C] | -30 |
| Krogla | Stainless steel |
| Ohišje | Nickel-plated brass |
| Potisni čep | Steel |
| Povezava | G 1/2 IT |
| Sprostilveni rokav | Steel |
| Tesnilo | NBR |
| Ventil | Brass |
| Vzmet | Stainless steel |
| DN | 12.5 |
| a/f [mm] | 33 |
| Volumski pretok (olja) [l/min] | 40 |
| Dolžina [mm] | 66.0 |
| Max. delovna temperatura [°C] | 100 |
| Max. obratovalni tlak [bar] | 300 |