



(slika je simbolična)

## Hitra spojka ID 7.8visok pretokR 1/4 Z.N.

Kategorija: [Quick disconnect coupling DN 7.8, male](#)  
Šifra: **107406RIE**

### Kratek opis

Quick-connect coupling I.D. 7.8, High flow rate, R 1/4 ET,  
Operating pressure 0 - 35 bar, Medium / ambient temp. -20  
°C to 40 °C

"

One-hand quick disconnect couplings, one side sealing, that  
combine high flow rates (approx. twice as high as the  
popular DN 7.2 standard coupling) with minimal coupling  
forces.

Suitable for all applications with an above-average air  
requirement!

To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

These quick disconnect couplings are not suitable for direct  
attachment to pulsating tools.

We recommend using our vibration dampers, according to  
ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant  
engineering, measurement, monitoring and control systems,  
manufacturing industry, medical technology, chemical /  
pharmaceutical industry, workshops, automotive, food  
technology, aerospace.

"

### Tehnične Specifikacije

|                                 |   |
|---------------------------------|---|
| Min. sobna temperatura<br>[°C]  | -20   |
| Min. temperatura medija<br>[°C] | -20   |
| Krogla                          | Stainless steel<br>at 6 bar and $\Delta p = 0.5$<br>bar |
| Merjenje pretoka                | Nickel-plated brass                                     |
| Navojni kos                     | G 1/4 ET  |
| Povezava                        | Stainless steel   |
| Pritrdilni obroč                | Brass   |
| Sedež ventila                   | Extremely robust,<br>ergonomic plastic                  |
| Sprostivni ročaj                | Steel, QPQ treated                                      |
| Telo ventila                    | NBR   |
| Tesnilo                         | Brass   |
| Ventil                          | Brass   |
| Vzmet                           | Stainless steel   |
| DN                              | 7.8   |
| a/f [mm]                        | 19  |
| Max. obratovalni tlak [bar]     | 35  |
| Max. sobna temperatura<br>[°C]  | 40  |
| Max. temperatura medija<br>[°C] | 40  |
| Dolžina [mm]                    | 65.0  |
| Pretok                          | 2100 l/min (air)  |