TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 29.11.2026



(slika je simbolična)

Hitre spojke I.D. 10, /poniklanaMedenina, G 1/2 notranji navoj

Kategorija: Quick disconnect coupling DN 10, female
Šifra: **141557RIE**

Kratek opis

Quick-connect coupling I.D. 10, Steel / nickel-plated brass, G 1/2 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C
"
Single-sided blocking and robust quick connect coupling with high flow performance.
To prevent injuries or a ""whiplash"" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.
These quick disconnect couplings are not suitable for direct attachment to pulsating tools.
We recommend using our vibration dampers, according to ISO 6150 § 7.1.
Areas of application: Pneumatic system, Machine and plant engineering, Measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, food technology, aerospace.
"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 - 35 bar
Merjenje pretoka	at 6 bar and Δ_p = 0.5 bar
Navojni kos	Nickel-plated brass
Ohišje	Nickel-plated brass
Povezava	G 1/2 IT
Rokav	Galvanised steel
Tesnilo	NBR
Ventil	Nickel-plated brass
Vzmet	Stainless steel
DN	10
a/f [mm]	24
Dolžina [mm]	62.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	3500 l/min (air)