TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 29.11.2026



(slika je simbolična)

Hitre spojke I.D. 10Visok przun. navojokG 3/4 N.N.

Kategorija: Quick disconnect coupling DN 10, female
Šifra: **107446RIE**

Kratek opis

Quick-connect coupling I.D. 10, High flow rate, Steel / nickel-plated brass, G 3/4 IT, Pressure 0 - 35 bar, Temp. -20 °C to 100 °C
"
One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. 3.5 times as high as the popular DN 7.2 standard coupling) with minimal coupling forces.
Suitable for all applications with an above-average air requirement!
To prevent injuries or a ""whiplash"" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.
These quick disconnect couplings are not suitable for direct attachment to pulsating tools.
We recommend using our vibration dampers, according to ISO 6150 § 7.1.
Areas of application: Pneumatic system, Machine and plant engineering, Measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, food technology, aerospace.
"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and Δ_p = 0.5 bar
Navojni kos	Nickel-plated brass
Povezava	G 3/4 IT
Pritrdilni obroč	Stainless steel
Sedež ventila	Brass
Sprostitveni rokav	Nickel-plated brass
Telo ventila	Steel, QPQ treated
Tesnilo	NBR
Ventil	Brass
Vzmet	Stainless steel
DN	10
a/f [mm]	32
Max. obratovalni tlak [bar]	35
Dolžina [mm]	73.7
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	3600 l/min (air)