



Hitre spojke I.D. 12, Garažna spojka, G 3/4 notranji navoj

Kategorija: [Quick disconnect coupling DN 12, female](#)
Šifra: **107480RIE**

(slika je simbolična)

Kratek opis

Quick-connect coupling I.D. 12, Garage coupling, Bright brass, G 3/4 IT, Pressure max. 16 bar, Medium/ambient temp. -10°C to 50°C

"

One-hand quick disconnect couplings, one side sealing, for high flow rates.

With rubber ring to protect against wear.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Machine and plant engineering, manufacturing industry, workshops.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Material	Brass with a bare metal surface at 6 bar and $\Delta_p = 0.5$
Merjenje pretoka	bar
Povezava	G 3/4 IT
Tesnilo	NBR
Vzmet	Stainless steel
DN	12
Max. obratovalni tlak [bar]	16
a/f [mm]	30
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
Dolžina [mm]	82.0
Pretok	4150 l/min (air)