

Datum: 19.04.2026



(slika je simbolična)

Hitre spojke I.D. 2.7, Inox 1.4305, cev 5x3

Kategorija: [Quick disc. coupling DN2.7, 1.4305, hose connector](#)Šifra: **156211RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, Hose connection 5x3, Operating pressure 0 - 35 bar, Temp. -20°C to 200°C

"

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

"

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Delovni tlak | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla | Stainless steel 1.4034 |
| Merjenje pretoka | at 6 bar and $\Delta p = 1$ bar |
| Ohišje | Stainless steel 1.4305 |
| Povezava | Hose connection 5x3 |
| Pritrdilni obroč | Stainless steel 1.4310 |
| Rokav | Stainless steel 1.4305 |
| Telo ventila | Stainless steel 1.4305 |
| Tesnilo | FPM |
| Vzmet | Stainless steel 1.4310 |
| DN | 2.7 |
| a/f [mm] | 9 |
| Dolžina [mm] | 33.0 |
| Pretok | 120 l/min (air) |
| Max. sobna temperatura [°C] | 200 |
| Max. temperatura medija [°C] | 200 |