

Datum: 16.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[Hitre spojke I.D. 2.7, Nerjavno jeklo 1.4305, G 1/8 notranji navoj](#)

Kategorija: [Quick disconnect coupling DN 2.7, 1.4305, female](#)
Šifra: **156207RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, G 1/8 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 200 °C

"

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel 1.4034
Merjenje pretoka	at 6 bar and $\Delta p = 1$ bar
Ohišje	Stainless steel 1.4305
Povezava	G 1/8 IT
Pritrdilni obroč	Stainless steel 1.4310
Rokav	Stainless steel 1.4305
Telo ventila	Stainless steel 1.4305
Tesnilo	FPM
Vzmet	Stainless steel 1.4310
DN	2.7
a/f [mm]	12
Dolžina [mm]	28.0
Pretok	120 l/min (air)
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200