

Datum: 05.06.2026



(slika je simbolična)

Hitre spojke I.D. 2.7, Nerjavno jeklo 1.4404, G 1/8 notranji navoj

Kategorija: [Quick disconnect coupling DN 2.7, 1.4404, female](#)
Šifra: **107110RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, Stainless steel 1.4404, G 1/8 IT, Operating pressure 0 - 35 bar, Temp. -15 °C to 200 °C

"

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel 1.4404
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Stainless steel 1.4404
Povezava	G 1/8 IT
Pritrdilni obroč	Stainless steel 1.4404
Rokav	Stainless steel 1.4404
Telo ventila	Stainless steel 1.4404
Tesnilo	FKM
Vzmet	Stainless steel 1.4404
DN	2.7
a/f [mm]	12
Dolžina [mm]	28.0
Pretok	165 l/min (air)
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200