TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 15.11.2026



(slika je simbolična)

Hitre spojke I.D. 2.7,Nerjavno jeklo 1.4404, G 1/8 zunanji navoj

Kategorija: Quick disconnect coupling DN 2.7, 1.4404, male
Šifra: **107108RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, Stainless steel 1.4404, G 1/8 ET, Operating pressure 0 - 35 bar, Temp. -15 °C to 200 °C
"
One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.
To prevent injuries or a ""whiplash"" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.
Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.
"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel 1.4404
Merjenje pretoka	at 6 bar and Δ_p = 0.5 bar
Ohišje	Stainless steel 1.4404
Povezava	G 1/8 ET
Pritrdilni obroč	Stainless steel 1.4404
Rokav	Stainless steel 1.4404
Telo ventila	Stainless steel 1.4404
Tesnilo	FKM
Vzmet	Stainless steel 1.4404
DN	2.7
a/f [mm]	11
Dolžina [mm]	28.0
Pretok	165 l/min (air)
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200