



(slika je simbolična)

[Hitre spojke I.D. 2.7, ponikljana medenina, M5 notranji navoj](#)

Kategorija: [Quick disconnect coupling DN 2.7, female](#)
Šifra: **107089RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, nickel-plated brass, M5 IT,
Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

One-hand quick disconnect couplings, one side sealing,
extremely compact with a large bore and only a small
pressure drop.

To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

Areas of application: Pneumatic system, machine and plant
engineering, measurement, monitoring and control systems,
manufacturing industry, medical technology, chemical /
pharmaceutical industry, automotive.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Delovni tlak | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla | Stainless steel |
| Merjenje pretoka | at 6 bar and $\Delta_p = 0.5$ bar |
| Ohišje | Nickel-plated brass |
| Povezava | M5 IT |
| Pritrdilni obroč | Stainless steel |
| Rokav | Nickel-plated brass |
| Telo ventila | Nickel-plated brass |
| Tesnilo | NBR |
| Vzmet | Stainless steel |
| DN | 2.7 |
| a/f [mm] | 9 |
| Dolžina [mm] | 25.0 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |
| Pretok | 165 l/min (air) |