

Datum: 02.06.2026



(slika je simbolična)

[Hitre spojke I.D. 2.7, ponikljana medenina, M5 zunanji navoj](#)

Kategorija: [Quick disconnect coupling DN 2.7, male](#)
Šifra: **107087RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, nickel-plated brass, M5 ET,
Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C
"

One-hand quick disconnect couplings, one side sealing,
extremely compact with a large bore and only a small
pressure drop.

To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

Areas of application: Pneumatic system, machine and plant
engineering, measurement, monitoring and control systems,
manufacturing industry, medical technology, chemical /
pharmaceutical industry, automotive.
"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta_p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	M5 ET
Pritrdilni obroč	Stainless steel
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
DN	2.7
a/f [mm]	9
Dolžina [mm]	26.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	165 l/min (air)