



(slika je simbolična)

Hitre spojke I.D. 5 »connect line«, cev 6x4

Kategorija: [Quick disconnect coupling DN 5 with hose connector](#)
Šifra: **115640RIE**

Kratek opis

Quick-connect coupling I.D. 5 »connect line«, bright brass,
Hose 6x4, Operating pressure 0 - 35 bar, Temp. -20 °C to
100 °C

Low-priced, one-hand quick disconnect couplings, one side
sealing, compact with a large bore and only a small
pressure drop.

To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

Areas of application: Pneumatic system, measurement,
monitoring and control systems, manufacturing industry,
medical technology, chemical / pharmaceutical industry,
automotive, food technology.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	Hose connection 6x4
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
Zaporni zatič DN	Stainless steel
a/f [mm]	5
Dolžina [mm]	14
Max. sobna temperatura [°C]	42.4
Max. temperatura medija [°C]	100
Pretok	100
	560 l/min (air)