

Datum: 01.05.2025

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Hitre spojke I.D. 5 »connect line«, cev I.D. 6

Kategorija: [Quick disconnect coupling DN 5, with hose stem](#)  
Šifra: **115636RIE**

### Kratek opis

Quick-connect coupling I.D. 5 »connect line«, bright brass, Sleeve I.D. 6, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"  
Low-priced, one-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

"

### Tehnične Specifikacije

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -20                                                          |
| Min. temperatura medija [°C] | -20                                                          |
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Merjenje pretoka             | at 6 bar and $\Delta_p = 0.5$ bar                            |
| Ohišje                       | Brass with a bare metal surface                              |
| Povezava                     | I.D. 6                                                       |
| Pritrdilni obroč             | Stainless steel                                              |
| Rokav                        | Brass with a bare metal surface                              |
| Telo ventila                 | Brass with a bare metal surface                              |
| Tesnilo                      | NBR                                                          |
| Vzmet                        | Stainless steel                                              |
| Zaporni zatič                | Stainless steel                                              |
| DN                           | 5                                                            |
| a/f [mm]                     | 14                                                           |
| Dolžina [mm]                 | 46.9                                                         |
| Max. sobna temperatura [°C]  | 100                                                          |
| Max. temperatura medija [°C] | 100                                                          |
| Pretok                       | 560 l/min (air)                                              |