

Datum: 24.05.2026



(slika je simbolična)

Hitre spojke I.D. 5, Nerjavno jeklo 1.4305, G 1/4 notranji navoj

Kategorija: [Quick disconnect coupling DN 5, 1.4305, female](#)
Šifra: **107196RIE**

Kratek opis

Quick-connect coupling I.D. 5, Stainless steel 1.4305, G 1/4 IT, Operating pressure 0 - 35 bar, Temp. -15 °C to 200 °C

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305, compact with a large bore. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Tehnične Specifikacije

| | |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C] | -15 |
| Min. temperatura medija [°C] | -15 |
| Delovni tlak | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla | Stainless steel |
| Merjenje pretoka | at 6 bar and $\Delta p = 0.5$ bar |
| Ohišje | Stainless steel 1.4305 |
| Povezava | G 1/4 IT |
| Pritrdilni obroč | Stainless steel |
| Rokav | Stainless steel 1.4305 |
| Telo ventila | Stainless steel 1.4305 |
| Tesnilo | FKM |
| Vzmet | Stainless steel |
| DN | 5 |
| a/f [mm] | 17 |
| Dolžina [mm] | 38.0 |
| Max. sobna temperatura [°C] | 200 |
| Max. temperatura medija [°C] | 200 |
| Pretok | 560 l/min (air) |