

Datum: 26.09.2024



(slika je simbolična)

[Hitre spojke I.D. 5, ponikljana medenina, toga, cev 8x6](#)

Kategorija: [Quick disconnect coupling DN 5 with hose connector](#)
Šifra: **107172RIE**

Kratek opis

Quick-connect coupling I.D. 5, nickel-plated brass, rigid,
Hose connection 8x6, Operating pressure 0-35 bar, Temp.
-20°C to 100°C

One-hand quick disconnect couplings, one side sealing,
compact with a large bore and only a small pressure drop.
To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

Areas of application: Pneumatic system, measurement,
monitoring and control systems, manufacturing industry,
medical technology, chemical / pharmaceutical industry,
automotive, food technology.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	Hose connection 8x6
Pritrdilni obroč	Stainless steel
Različica	Rigid
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
a/f [mm]	14
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Dolžina [mm]	132.0
Pretok	560 l/min (air)