

Datum: 04.04.2026



Hitre spojke I.D. 5 zakl. na obeh str.G 1/4 N.N.

Kategorija: [Quick disconnect coupling DN5, bright brass female](#)
Šifra: **107495RIE**

(slika je simbolična)

Kratek opis

Quick-connect coupling I.D. 5, locking on both sides, Bright brass, G 1/4 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C

Both the coupling and the self-sealing plug are fitted with a valve.

Connection: Both valves open and the medium is allowed to pass.

Disconnection: Both valves close and the medium is prevented from escaping.

Areas of application: Pneumatic system, machine and plant engineering, Measurement, monitoring and control systems, Manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	G 1/4 IT
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
a/f [mm]	17
Dolžina [mm]	38.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	310 l/min (air)