

Datum: 13.06.2026



(slika je simbolična)

Hitre spojke I.D. 5 zakl. na obeh str.G 1/4 Z.N.

Kategorija: [Quick disconnect coupling DN 5, bright brass, male](#)
Šifra: **107493RIE**

Kratek opis

Quick-connect coupling I.D. 5, locking on both sides, Bright brass, G 1/4 ET, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C

Both the coupling and the self-sealing plug are fitted with a valve.

Connection: Both valves open and the medium is allowed to pass.

Disconnection: Both valves close and the medium is prevented from escaping.

Areas of application: Pneumatic system, machine and plant engineering, Measurement, monitoring and control systems, Manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Delovni tlak | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla | Stainless steel |
| Merjenje pretoka | at 6 bar and $\Delta p = 0.5$ bar |
| Ohišje | Brass with a bare metal surface |
| Povezava | G 1/4 ET |
| Pritrdilni obroč | Stainless steel |
| Rokav | Brass with a bare metal surface |
| Telo ventila | Brass with a bare metal surface |
| Tesnilo | NBR |
| Vzmet | Stainless steel |
| DN | 5 |
| a/f [mm] | 17 |
| Dolžina [mm] | 38.0 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |
| Pretok | 310 l/min (air) |