

Datum: 17.03.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Hitre spojke I.D. 5, zunanji navoj medenina, toga, cev 8x6

Kategorija: [Quick disconnect coupling DN 5 with hose connector](#)  
Šifra: **107142RIE**

### Kratek opis

Quick-connect coupling I.D. 5, bright brass, rigid, Hose connection 8x6, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"  
One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

"

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	Hose connection 8x6
Pritrdilni obroč	Stainless steel
Različica	Rigid
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
a/f [mm]	14
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Dolžina [mm]	132.0
Pretok	560 l/min (air)