

Datum: 02.07.2026



(slika je simbolična)

Hitre spojke I.D. 5, zunanji navoj medenina, vrteče, cev 8x6

Kategorija: [Quick disconnect coupling DN 5 with hose connector](#)
Šifra: **107144RIE**

Kratek opis

Quick-connect coupling I.D. 5, bright brass, rotating, Hose connection 8x6, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	Hose connection 8x6
Pritrdilni obroč	Stainless steel
Različica	Swivelling 360°
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
a/f [mm]	14
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Dolžina [mm]	145.0
Pretok	560 l/min (air)