



(slika je simbolična)

Hitre spojke I.D. 5ponikljana medenina, G 3/8 zunanji navoj

Kategorija: [Quick disconnect coupling DN 5, male](#)
Šifra: **107160RIE**

Kratek opis

Quick-connect coupling I.D. 5, nickel-plated brass, G 3/8 ET, Operating pressure 0-35 bar, Med./ambient temp. -20°C to 100°C

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Delovni tlak | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla | Stainless steel |
| Merjenje pretoka | at 6 bar and $\Delta_p = 0.5$ bar |
| Ohišje | Nickel-plated brass |
| Povezava | G 3/8 ET |
| Pritrdilni obroč | Stainless steel |
| Rokav | Nickel-plated brass |
| Telo ventila | Nickel-plated brass |
| Tesnilo | NBR |
| Vzmet | Stainless steel |
| DN | 5 |
| a/f [mm] | 19 |
| Dolžina [mm] | 38.0 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |
| Pretok | 560 l/min (air) |