

Datum: 28.05.2026



(slika je simbolična)

## Hitre spojke I.D. 5Z.N. Med.G 3/8 N.N.

Kategorija: [Quick disconnect coupling DN 5, female](#)  
Šifra: **107130RIE**

### Kratek opis

Quick-connect coupling I.D. 5, bright brass, G 3/8 IT,  
Operating pressure 0 - 35 bar, Med. / ambient temp. -20 °C  
to 100 °C

"  
One-hand quick disconnect couplings, one side sealing,  
compact with a large bore and only a small pressure drop.  
To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

Areas of application: Pneumatic system, measurement,  
monitoring and control systems, manufacturing industry,  
medical technology, chemical / pharmaceutical industry,  
automotive, food technology.

"

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	G 3/8 IT
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
a/f [mm]	19
Dolžina [mm]	40.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	560 l/min (air)